International Journal of All Research Education and Scientific Methods (IJARESM),
ISSN: 2455-6211, Volume 13, Issue 5, May-2025, Available online at: www.ijaresm.com

Industrial Automation using Robotic ARM Technology

Akshata Patil[1], Ashish Pawar[2], Prasad Shelake[2], Sandip Jong[2], Suhani Gade[2]

[1]Lecturer, Department of Electrical Engineering, Annasaheb Dange College of Engineering, Sangli, Maharashtra, India
[2]Undergraduate Student, Department of Electrical Engineering, Annasaheb Dange College of Engineering, Sangli, Maharashtra, India

---

ABSTRACT

This project presents an innovative automated object sorting system aimed at improving industrial productivity through the use of a conveyor belt setup. Objects are placed on the moving belt and proceed toward a precisely located sensor near the endpoint. This sensor identifies various attributes of the objects—such as their material, size, or shape—and transmits this information as input signals to a Programmable Logic Controller (PLC). Serving as the central processing unit, the PLC executes a predefined sorting program to determine the correct action for each item. Based on the programmed logic, it controls the conveyor and robotic arm motors to direct objects appropriately. When an object matches the set parameters, the robotic arm accurately picks it up and deposits it in the corresponding sorting section. Items that do not fulfill the required criteria are diverted to a rejection zone, ensuring an efficient and accurate sorting routine. The integration of a conveyor belt, sensitive detection sensors, a dependable PLC, and a responsive robotic arm contributes to the system's high efficiency and reliability. Additionally, the modular structure allows the system to manage a wide variety of objects, making it highly flexible and adaptable to shifting industrial needs.

Keywords- Robotic Arm , Industrial Automation , PLC , Conveyor Belt System ,Object Sorting System , Sensor Integration

INTRODUCTION

Robotic arms are advanced mechanical devices built to carry out diverse tasks with a high degree of accuracy and efficiency. Their structure includes multiple joints—either rotating or sliding—powered by actuators that enable movement. They also feature sensors that provide essential feedback and end effectors such as grippers or customized tools used for interacting with various objects. The arm's operations are controlled by systems like programmable logic controllers (PLCs) or advanced algorithms that manage motion and functionality. To boost their performance in handling more challenging and variable tasks, these robotic systems often incorporate vision technologies, force feedback mechanisms, and artificial intelligence (AI) capabilities.

In recent decades, robotic arm technology has versions were limited by basic mechanical frameworks and simplistic control systems, restricting their use to straightforward,

repetitive functions. Progress in materials engineering has paved the way for the creation of components that are not only lighter but also stronger and more resilient. The addition of sophisticated sensors and responsive feedback systems has enabled modern robotic arms to operate with enhanced precision and versatility. Furthermore, the integration of artificial intelligence and machine learning has transformed these systems, empowering them to take on intricate tasks, adapt through experience, and work collaboratively with humans.

Today, robotic arms play an essential role in a wide range of industries such as automotive production, electronics, pharmaceuticals, and food processing. experienced significant advancements. Initial solar This system represents an advanced automation framework designed to execute precise control tasks in industrial and robotics applications. At its heart is the Delta PLC (Programmable Logic Controller), a robust and programmable device that manages inputs and outputs to coordinate system operations. The PLC is powered by a centralized power supply, which ensures stable and consistent operation of all components.



Figure 1: Block Diagram of Industrial Automation Using Robotic Arm Technology

The IR sensor plays a critical role in detecting objects, changes in position, or specific environmental conditions. It sends real-time signals to the PLC, which processes this input to make decisions, such as initiating or halting motor movements. This sensor-based feedback allows the system to operate dynamically and adapt to varying scenarios.

For actuation, the system employs two types of motors: a servo motor and a stepper motor, each controlled by dedicated drivers. The servo driver communicates with the PLC to regulate the servo motor, which excels at achieving accurate angular positions and smooth motion, making it ideal for applications like robotic arms, conveyor belts, or automated positioning systems. On the other hand, the stepper motor, controlled by the microstep driver, is used for tasks requiring incremental, highly

Delta PLC : Delta Programmable Logic Controllers (PLCs), manufactured by Delta Electronics, are widely recognized for their reliability, versatility, and cost-effectiveness in industrial automation systems.

Servo Motor: A servo motor is a high- performance motor designed for precise control of position, speed, and torque. Unlike standard motors, which operate at a constant speed, servo motors use a closed-loop system with a feedback mechanism (such as an encoder or resolver) to continually monitor and adjust the motor’s movement.

Micro step driver : A microstep driver is an advanced type of motor driver that controls the current supplied to a stepper motor in small, precise increments or "microsteps." Unlike traditional stepper drivers that only control the motor in full or half-step increments, microstep drivers divide each step into smaller fractions, often as small as 1/256th of a full step.

Gear motor: A gear motor is a combination of an electric motor and a gear system, designed to provide

controlled torque and speed. The gear mechanism, usually a set of gears like planetary or spur gears, reduces the motor's output speed while increasing the torque. This makes gear motors highly effective for applications that require precise control over motion, such as robotics, conveyors, and automation system.

Objectives

1. To make the packaging process automatic.
2. To design the robotic arm.
3. Develop an Automated System.
4. Improve Sorting Accuracy.
5. Optimize Material Handling.
6. Enhance Operational Efficiency.

LITERATURE REVIEW

This article presents an in-depth analysis of industrial automation, with a particular emphasis on robotic arm technologies. It outlines the key advantages of incorporating robotic arms in industrial environments, such as improved precision and enhanced operational efficiency. The paper also delves into different control techniques and sensor integration approaches, examining both the benefits and the challenges encountered during their application. The goal is to offer a well- rounded perspective on the current advancements and future trends in robotic arm systems. In-Depth Review of Robotic Arm Technologies in Industrial Automation [1].

This case study explores the real-world application of a robotic arm system in an industrial context. It demonstrates how the technology contributes to increased efficiency and cost savings. The authors detail each stage final deployme.nt—along with performance assessments that validate the system's effectiveness. This example illustrates the practical potential of robotic arms in modern manufacturing and production environments. Case Study: Robotic Arm Integration in Industrial Processes [2].

PROPOSED WORK

While the current system is fully functional, there are several areas in which it could be improved and expanded to increase its capabilities and adaptability. The proposed work focuses on enhancing system efficiency, scalability, and the ability to handle a broader range of objects.

Energy-Efficient Operation
Energy efficiency is a key area of focus for future enhancements. The system can be improved by optimizing the control of motors and sensors to reduce overall energy consumption. For example, using energy- efficient motors for both the conveyor belt and the robotic arm can reduce the system's operational cost. Additionally, using low- power sensors will help lower the overall energy consumption while maintaining high performance.

Modular Design for Scalability
The current system is designed with scalability in mind. As industrial needs grow, the system can be expanded by adding additional conveyor belts, robotic arms, or sorting bins. This modular approach allows industries to scale the system up or down as needed. Future work will focus on making this modularity easier to implement, ensuring that the system can adapt to changing production demands. of the process—from conceptual design to

Handling a Broader Range of Objects
The system is designed to handle specific object sizes, shapes, and materials. However, there is room for improvement in expanding the range of objects that the system can sort. Future enhancements may include upgrading sensors to handle a broader range of object characteristics, such as varying weights or more complex shapes. This would make the system more versatile and capable of handling different industrial applications.

Increased Speed and Precision
The speed and precision of the robotic arm are key to the overall performance of the system. While the current robotic arm performs well, further improvements in its control and mechanics could make the system even faster and more precise. Enhancing the robotic arm's speed would increase throughput, while increasing precision would improve the accuracy of sorting.

Enhanced Safety Protocols
Safety is a critical aspect of industrial automation. Future enhancements could include the integration of additional safety protocols, such as emergency stop buttons and automatic shutoff systems. This will ensure that the system is safe to operate in industrial environments, especially when workers are present.

METHODOLOGY

The methodology for the automated object sorting system integrates a conveyor belt, sensors, a PLC (Programmable Logic Controller), and a robotic arm to sort objects efficiently based on their characteristics. The process is designed to optimize accuracy and speed while handling different types of objects in an industrial setting.

System Design

The project begins with the design of the conveyor belt, which is responsible for moving the objects along the sorting process. The conveyor belt ensures that the objects are consistently placed in the right position for sorting. This belt is powered by motors controlled by the PLC, which adjusts the speed and movement according to the system's requirements. The movement of the belt is synchronized with the action of the robotic arm to ensure precise sorting.The robotic arm is a crucial component of the system. It is designed to pick up objects from the conveyor belt and place them into designated bins based on the sorting criteria. The arm is equipped with a high-precision motor, which allows it to handle objects with minimal error. Its fast and efficient movements help maintain a high throughput.

Component Integration

The sensors used in the system are designed to detect specific characteristics of each object, such as size, shape, or material. These sensors are installed at the end of the conveyor belt, ensuring that each object is accurately identified before it reaches the robotic arm. The sensors relay the object information to the PLC, which processes the data.

The PLC, which acts as the system's control center, is responsible for receiving data from the sensors, interpreting it, and making decisions about how to handle each object. It uses pre-programmed sorting algorithms to determine if an object meets the criteria for sorting. Based on these decisions, the PLC sends output signals to control the conveyor belt motor and robotic arm motors.

PLC Programming

The core of the system lies in the PLC programming. The PLC is programmed using ladder logic, a widely used method in industrial automation. The ladder logic program allows the PLC to process sensor inputs and produce output signals to control the conveyor belt and robotic arm.The program is designed to evaluate whether an object meets the sorting criteria, such as being of a certain size or material. If the object meets the criteria, the PLC commands the robotic arm to pick the object and place it in the correct bin. If it doesn't meet the required criteria, the object is directed to the rejection area.

Robotic Arm Control

The robotic arm's movement is directly controlled by the signals from the PLC. When the PLC sends a signal indicating that an object should be sorted, the robotic arm picks up the object from the conveyor belt and places it in the appropriate bin. The robotic arm's high precision and speed enable it to perform these tasks with minimal downtime, making the sorting process highly efficient.

Testing and Calibration

Once the system is fully integrated, extensive testing is conducted to ensure that all components work together smoothly. The sensors are calibrated to ensure accurate object detection, and the robotic arm's movements are tested for precision. Additionally, the PLC program is refined to ensure that the sorting criteria are correctly implemented, and that the system responds correctly to different types of objects.

Calibration is performed to fine-tune the system's performance, ensuring that all components are optimized for maximum efficiency. After testing and calibration, the system is validated to confirm that it can perform the sorting task effectively in real- world industrial settings.

CONCLUSION

The outlook for industrial automation powered by robotic arms is highly promising, as ongoing technological advancements continue to expand their capabilities. With the shift toward more customized, on-demand, and eco-friendly manufacturing processes, robotic arms are set to play a crucial role in driving the future of production. However, unlocking the full potential of this technology requires more than just innovation—it calls for attention to human, ethical, and operational dimensions as well. Ensuring that automation contributes to both economic progress and positive societal outcomes is essential. While robotic arms will undoubtedly be central to next-generation automation systems, their effective implementation will rely on carefully balancing innovation with considerations like workforce implications, cybersecurity, and environmental responsibility.

Enhanced Productivity & Efficiency Robotic arms offer unparalleled speed, precision, and consistency in manufacturing tasks, leading to significant improvements in production rates and overall efficiency. Their ability to operate continuously without fatigue reduces downtime and optimizes resource utilization.Cost Reduction & Accessibility: As technology matures and costs decrease, even small and medium-sized enterprises (SMEs) will gain access to advanced automation

solutions, leveling the playing field and encouraging wider adoption of robotics in industries beyond just high- volume production. Improved Quality Control By minimizing human error, robotic arms ensure higher product consistency and better quality control. Advanced sensors, vision systems, and AI algorithms will enable robots to detect defects and perform precision tasks, elevating the standard of finished products.

ACKNOWLEDGMENT

We would like to express our deepest gratitude to several individuals who have been essential to the successful completion of this project.

First and foremost, we would like to thank our project guide, [Mrs.Akshata Patil], for their expert guidance and continuous support throughout the development of this project. Their deep knowledge in the field of automation and practical problem-solving approach were invaluable to the success of this work.

We would also like to express our sincere appreciation to the Head of the Department and faculty members of the Electrical Engineering Department at Annasaheb Dange College of Engineering & Technology, Ashta, for their encouragement and academic support. Their knowledge and resources have greatly aided in the execution of this project.

Special thanks to the lab technicians for their assistance in setting up and testing the system. Their expertise in handling the hardware components and troubleshooting was crucial to the smooth implementation of the system.

Lastly, we would like to extend our heartfelt thanks to our families for their continuous support and understanding during the course of this project. Their encouragement has motivated us to overcome challenges and complete this work successfully.

REFERENCES

[1]. A. K. Mishra et al., "Tuning of Robotic Arm Control System for Industrial Automation using Genetic Algorithm," IEEE Access, vol. 8, April 2020, pp. 56412-56423
[2]. S. S. Singh et al., "Small-Signal and Large-Signal Approaches for Robotic Arm Control in Industrial Automation," International Journal of Automation and Control, vol. 14, February 2022,pp. 215- 230.
[3]. J. H. Kim et al., "Control and Tuning of Robotic Arm for Welding in Industrial Automation," Journal of Manufacturing Processes, vol. 58, March 2020, pp. 365- 372.
[4]. H. Liu et al., "Industrial Automation using Robotic Arm via PLC: Challenges and Opportunities," Journal of Industrial Electronics, vol. 60, November 2019, pp. 1205-1216.
[5]. Y. Zhang et al., "Modulation Techniques for Robotic Arm Control in Industrial Automation: A Review," Journal of Automation and Control, vol. 17, July 2022, pp. 105-119.
[6]. S. S. Rao et al., "Tuning Methods for Robotic Arm Control in Industrial Automation: A Review," Control Engineering Practice, vol. 44, June 2020, pp. 70-82.
[7]. H. S. Kim et al., "TecnoGogly Robotic Arm for Packaging in Industrial Automation," Journal of Robotics and Automation, vol. 50, October 2019, pp. 145-152.
[8]. R. Kumar et al., "Industrial Automation using TecnoGogly Robotic Arm: A Review of Safety and Automation and control, vol. 14, July 2022, pp. 105-120.